

BATTERY ACCESSORIES

ELECTRICAL

D

In Section D:	Meters/Testers	Wiring	Fuses	12V Accessories	Battery Accessories	Chargers & Inverters	Cords & Adapters	Box/Hatch	Switches
---------------	----------------	--------	-------	-----------------	---------------------	----------------------	------------------	-----------	----------

Designed for the RV Owner!

SURE POWER BATTERY ISOLATORS & SEPARATORS

BATTERY ISOLATORS ELIMINATE MULTI-BATTERY DRAIN

When 2 or more battery banks are in a charging system you can get stuck with dead batteries and an engine that won't start IF YOU DON'T HAVE a battery isolator. •SOLID STATE ELECTRONICS means no moving parts to wear out! •UNIQUE DESIGN: The anodized fin design provides maximum heat dissipation *plus* all electrical parts are sealed with a moisture-proof epoxy sealant to preserve them from the elements. •ALLOWS EACH BATTERY TO DISCHARGE AND CHARGE ACCORDING TO ITS OWN NEEDS.



TWO-BATTERY STANDARD ISOLATOR

15776 70-Amp CS** #702-D 24

TWO-BATTERY UNIVERSAL ISOLATORS

15777 95-Amp CS** #9523A-D 24

15778 120Amp CS** #12023A-D 12

APPLICATION INFORMATION

GROUP 1	General Motors (Delcotron)	Except Delcotron CS series alternators (CS series used on most 1985 and newer GM vehicles).
	Ford	Up to 1998.
	Chrysler	All models, all years including Nippondenso externally regulated alternators.
	Jeep	Equipped with Nippondenso externally regulated alternators.
	Japanese Imports	With alternators using external voltage regulator or external sensing.
	Motorola	Load Handler Series or 8EM Remote Sense Series.
A Group 1 Isolator will have an alternator post and up to four battery posts. There are no colored terminals.		
GROUP 2	General Motors (Delcotron)	Equipped with Delcotron CS Series (most 85-93) or SC130-D series alternators (most 93 & newer**)
	Jeep	Vehicles equipped with Delcotron CS series alternator (most 1985-90).
	Toyota, Honda & Some Imports	1985 and newer equipped with Nippondenso alternator with internal regulators or alternators with an "S" (sense) terminal.
	Ford	Many 1998 and newer.
	Unplugging the plug-in connector from the alternator and counting the number of holes in the connector can identify the CS series alternator. The CS series will have three small and one large hole. The CS130-D alternator has four pin terminals all the same size. The SI series will have two slotted holes in the connector. **Delco CS series alternators require a separate sense wire which is included with the connector kit. The connector kit may or may not be included with the isolator, but is available as an accessory. All Group 2 isolators may be used in Group 1 applications. Simply disregard the additional excitation ("E") terminal. A group 2 Isolator will have a colored fourth terminal indicating the "E" terminal.	

MAXIMUM ALTERNATOR RATING	2 BATTS 1 Main, 1 Aux.	RECOMMENDED WIRE SIZE / CIRCUIT BREAKER			
		Up to 15'	15' to 20'	20' to 25'	25' to 30'
70 Amps	15776	#8-ga. / 50Amp	#8-ga. / 50Amp	#6-ga. / 50Amp	#6-ga. / 50Amp
95 Amps	15777	#8-ga. / 50Amp	#6-ga. / 50Amp	#4-ga. / 50Amp	#4-ga. / 50Amp
120 Amps	15778	#6-ga. / 80Amp	#4-ga. / 80Amp	#2-ga. / 80Amp	#1-ga. / 80Amp
160 Amps		#4-ga. / 120Amp	#2-ga. / 120Amp	#2-ga. / 120Amp	#0-ga. / 120Amp
240 Amps		#000 ga. / 150 Amp	#000 ga. / 150 Amp	#0000 ga. / 150 Amp	#0000 ga. / 150 Amp

SMART SOLENOID BATTERY SEPARATOR

The Smart Solenoid is available in two models, a uni-directional charging model and a bi-directional charging model. The uni-directional model charges auxiliary battery after the primary battery has reached at least 13.2-V. The primary battery is the priority charged battery. The bi-directional charger charges primary and auxiliary battery after either battery has reached 13.2-V. This model is particularly useful for motorhomes or other vehicles which are equipped with an auxiliary battery charger, generator, inverters or solar chargers. Mounts on tow vehicle or towable.

Order #	SMART SOLENOID MODELS
17715	Uni-Directional (charges starting battery, then auxiliary)
17716	Bi-Directional (activates when either battery is charging)



E-SERIES BATTERY SWITCHES

Up to 350 Amperes Continuous Rating

Ignition protected - safe for installation aboard gasoline powered boats. Tactile indicator conveys knob position by feel only. Fits all Perko and Guest low amperage battery switch hole patterns. Case design allows surface or rear panel-mounting. Accepts up to 4/0 AWG (95mm2) battery cables. • Meets American Boat and Yacht Council (ABYC) requirements for battery switches. • Make-before-break contact design on 9001 and 9002 models allows switching between battery banks without power interruption.

APPLICATIONS 12533

1. Switches battery bank 1 or battery bank 2 or battery banks 1 and 2 to all loads using one switch.

APPLICATIONS 13013

1. Switches a single battery to a single load group. 2. Can be used in multiples to manage several isolated circuits including cross connecting for emergency paralleling.

SPECIFICATIONS	9001e-9003e
Inrush Rating: 0.25 sec (10 repeats)*	1,750 Amperes DC
Cranking Rating: 9.75 sec (10 repeats)*	900 Amperes DC
Intermittent Rating: 5 min (UL 1107)	600 Amperes DC
Continuous Rating: (UL 1107)	350 Amperes DC
Terminal Stud Size	3/8"-16 (M10)
Terminal Stud Torque	140 in-lbs.
Cable Size to Meet Ratings***	4/0
Voltage Rating	48 Volts DC Maximum
Cable Clearance For 4/0 Cables	1.10" (27.9mm)
Case Material	Reinforced Polycarbonate
CE marked	
AGENCY STANDARDS	
UL Listed - UL 1107 electric power switches**	
Meets UL 1500 and SAE J1171 external ignition protection requirements	
* Blue Sea Systems Engine Starting Standard	
** Per Circuit	
*** Reducing cable size will reduce current rating	

E-Series Battery Switch:


12533 Selector #9001E 5

13013 Single Circuit On/Off #9003E 5

M-SERIES BATTERY SWITCHES

300 AMPERES CONTINUOUS RATING

All switches have: • Ignition protected - Safe for installation aboard gasoline powered boats. • Tactile textures indicate knob position by feel only. • Case design allows surface, front panel, or rear panel mounting. • Label with international ON/OFF legends. • Ideal for marine or RV applications. • Accepts up to 4/0 AWG battery cables. • All non-corrosive marine grade metals. • Molded in durable reinforced polycarbonate. • ICON label set included for circuit identification. • Removable key or knob remains positively retained. • 3/8"-16 M10 tin-plated copper studs for maximum conductivity and corrosion resistance. • 7/8" Long stud length to accept multiple cable terminals. • Isolator cover with snap-in sections protects rear contacts.



APPLICATIONS (14548-14549)

1. Switches a single battery to a single load group.
2. Multiple switches can be used to manage several isolated circuits including cross connecting for emergency paralleling.



14578

APPLICATION (14578)

1. Switches battery bank 1 or battery bank 2 or battery banks 1 and 2 to all loads using one switch.

M-Series Battery Switch:

- 14548** Single Circuit On-Off w/Key #6005 5
14549 Single Circuit On-Off, w/Knob #6006 1
14578 Selector #6007 5

SPECIFICATIONS	
Inrush Rating: 0.25 sec (10 repeats)*	1,500 Amperes DC
Cranking Rating: 9.75 sec (10 repeats)*	700 Amperes DC
Intermittent Rating: 5 min (UL 1107)	500 Amperes DC
Continuous Rating: (UL 1107)	300 Amperes DC
Maximum Voltage Rating	48 Volt DC
Terminal Stud, Tin-Plated Copper	3/8" -16 (M10)
Terminal Stud Torque	140 in-lb.
Cable Size to Meet Ratings***	4/0 AWG
Cable Clearance For 4/0 Cables	1.12" (28.4mm)
Case Material	Reinforced Polycarbonate
CE marked	
AGENCY STANDARDS	
UL Listed - UL 1107 electric power switches. Meets UL 1500 and SAE J1171 external ignition protection requirements. * Blue Sea Systems Engine Starting Standard ** Per Circuit *** Reducing cable size will reduce current rating	



PROGRESSIVE DYNAMICS RV & MARINE AUTOMATIC TRANSFER RELAY SYSTEM

Generator to shore power automatic transfer relay system features: • Heavy duty relays to prevent contact damage during high current transfer operation. • Quick change replaceable circuit board. • Time delay circuit board ensures generator voltage is at proper level before transfer occurs. • Built-in strain reliefs for easy installation. • Protective cover easily snaps on or off. • PD5110010V has pigtail AC wire connections.

12375 Automatic Transfer Relay System, 120VAC, 30Amp #PD5110010V 1

14945 Automatic Transfer Relay System, 120VAC, 50Amp #PD52V 4


PARALLAX POWER SUPPLY



A Division of Connecticut Electric, Inc.

BATTERY DISCONNECT RELAY

Prevents battery drain during camping and storage periods. • Helps maintain battery life. • No continuous current draw. • 100A 12VDC capability continuous. • 300 amp surge.



15009 Battery Relay #BR100 1

POLLAK SOLENOID SWITCHES - CONTINUOUS DUTY

- 6-24 VDC Systems
- Plated Steel or Phenolic Housings
- Ignition & Ground Terminals, No.10-32 Thread
- Contact Terminals 5/16"- 24 Thread
- Bracket Mounting Holes; 5/16" x 19/32", 2 1/8" on centers.
- Complete Mounting Hardware.

Starter Solenoid, Continuous Duty 85 Amps, 4 terminal, UL listed:

13753 Bulk #52-307 25

13785 Visi-Pak #52-307V 1

Starter Solenoid (Same as 52-307 except grounded), 3 terminal, not UL listed:

13678 Bulk #52-312 50



Pollak

SPECIFICATIONS	
Voltage Rating:	6-24 VDC
Features:	12-V Continuous Duty Solenoid Insulated, with hardware. Flat Bracket. Replaces: Delco 1114218, 223; Prestolite 15-132,133, 236, 311, SAS-4201, 4202, 4213, 5203.Except grounded with three terminals. Replaces Presolite No's 15-139 SAS 4208.
Current Rating:	85 DC Amp
In Rush Current:	150 Amp

In Section D:	Meters/Testers	Wiring	Fuses	12V Accessories	Battery Accessories	Chargers & Inverters	Cords & Adapters	Box/Hatch	Switches
---------------	----------------	--------	-------	-----------------	---------------------	----------------------	------------------	-----------	----------



PARALLAX 500 SERIES POWER CENTERS

Parallax Power Centers - combining power conversion, battery charging, and AC/DC distribution - are a benchmark for RV power. 500 Series Power Centers for 50 amp/240 volt service are the most versatile yet, with eight AC branches, 15 DC fuse circuits, and a 50Amp main AC breaker. Add-ons like roof air conditioning, washers and dryers are accommodated. Extra panels are rarely needed. Filtered DC output is ideal for electronic-based appliances, accessories and motors. Power is free from spikes and surges, and operation is quiet. Smooth appliance operation and bright lighting are two of the benefits RVers appreciate. FCC Class B certification attests that minimal signal interference is caused with TVs, radios and emergency channels. c-ETL-us listed.

MODEL 555

- DC Output: 55 Amps. • AC Input: 120/240 Volts. • 8 AC Branches. • 15 DC Fuse Locations.
- 12-1/8" H x 12-1/4" W x 8-5/8" D. • 22 lbs.

16199 55 Amp. DC Output #555 1

The Perfect Power Solution for Smaller RV Classes.



PARALLAX POWER SUPPLY 6730 SERIES ELECTRONIC CONVERTER/CHARGER with AC and DC Distribution

- Filtered power is free from spikes and surges, and the full output rating is available for battery charging. • 30 amp DC output is ideal for smaller RVs. • Pre-wired circuit breakers are provided: (1) 30 amp main, (1) 20 amp branch, and (2) 15 amp branches. • Locations for five DC fuses (fuses not included); (1) fuse for reverse polarity protection is included. • 13.75" W, 7" H, 5.5" D; Cut-out required: 12.75" W, 6.25" H. Weight: 8 lbs.

15010 30 Amp Converter #6730D 1



10129

PARALLAX POWER SUPPLY 7155 SOLID POWER CENTER

30 AMP AC-55 AMP DC ELECTRONIC POWER CENTER

Direct OEM Replacement Part

- 30 amp AC service with 55 amp on the DC side.
- Distribution panel accommodates a 30 amp main AC circuit breaker. • Has a 5 AC branch circuits and 11 DC fuse circuits. • Weights: 13.5 lbs.
- Dim.: 11-3/4" H x 14" W x 7" D.

10129 55 Amp Converter with Distribution Panel #7155 1

55 AMP REPL. CONVERTER SECTION

For WFCO® WF-8945 and WF-8955 Power Centers

- Direct lower section replacement.
- Weights: 4.3 lbs. • 2-year warranty.
- Dim.: 9.5" L x 7" D x 4" H.

10131 Replacement Lower Section f/7155 #081-7155-000 1



PARALLAX POWER SUPPLY 500 SERIES REPLACEMENT CONVERTER SECTIONS

These converter/charger sections are direct replacements for the lower sections of Parallax 555 and 565 Power Centers. Filtered DC output is ideal for electronic-based appliances, accessories and motors.

500 Series Converter/Charger Only:

16200 55 Amp. DC Output, 12 lbs #555R 1



7300RU sections easily install into 6300 Series electronic power centers. A simple way to upgrade the popular 6300, 7300RU sections.

PARALLAX POWER SUPPLY 7300RU (REPLACEMENT UPGRADE) Electronic Converter/Charger Sections for Power Centers

An Easy Upgrade to Clean, Quiet Power.

- Upgrades linear power centers to electronic performance. • Provides filtered electronic power to existing power centers. • Power is free from spikes and surges, and the full output rating is available for battery charging. • Minimizes interference with TVs, radios, and emergency channels per FCC Class B certification.
- Quiet operation. The only sound comes from a small cooling fan. • DC Output is 14.0 max. volts @ no load, 13.2 volts max. at full load.
- The included fuse panel provides two 30 amp fuses for reverse polarity battery protection and capability up to nine DC load branch circuits.
- Two-year warranty.

Converter/Charger Lower Section & Upgrade:

18024 45 Amp. Output #7345RU 1

12411 55 Amp. Output #7355 RU 1

REPLACEMENT DOOR LATCH FOR CONVERTERS



14985 Door Latch #13516372

**PARALLAX
7400 SERIES DECK-MOUNTED
CONVERTER/ CHARGER**
The Most Proven Power...
Quiet, Clean, and Clear.

**PARALLAX®
POWER
SUPPLY**
A Division of Connecticut Electric, Inc.



- Filtered DC power is free from spikes and surges.
- Full output rating is available for battery charging.
- Minimal signal interference with TVs, radios, and emergency channels per FCC Class B certification.
- Quiet operation. The only sound comes from the cooling fan.
- c-ETL-us listed.
- Optional two-step charging provides expedient recharging and reliability through long-term park and storage periods.
- Dimensions: 4-1/8" H x 7" W x 12-3/8" L; . Weighs just 7.5 pounds
- Mounts in any position, including upside-down.
- Two-year warranty.

**PARALLAX®
POWER
SUPPLY**
A Division of Connecticut Electric, Inc.

Safety and
Convenience
for Power Transfer.



**PARALLAX
POWER
SUPPLY
LINE GENERATOR
SWITCHES**

MODEL ATS™ 301

- For 30Amp, 120-volt electrical systems —**
- Allows changeover of power between shoreline cord and generator controlled from inside the RV.
 - Can be used as deck-mount or mounted to the back of Parallax Power Centers.
 - Reliable electronic operation.
 - Generator time delay for load stabilization.
 - Chatter-free operation under low line voltage conditions.
 - Weight: 3.5 lbs.
 - 6" W x 4-1/8" D x 4-7/16" H.

14611 ATS 301 Line Generator Switch,
30 Amp./120 Volt #ATS301 [4](#)

Order #	Model	Description	AC Input		DC Output	
			Volts	Watts	Volts	Amps
12899	#7430	30 Amp Converter/Charger	105-130 60Hz	490	13.85 max. @ no load 13.2 min. @ full load	30
12412	#7440	40 Amp Converter/Charger	105-130 60Hz	670	13.85 max. @ no load 13.2 min. @ full load	40
18186	#7445	45 Amp Converter/Charger	105-130 60Hz	775	13.85 max. @ no load 13.2 min. @ full load	45
18187	#7455	55 Amp Converter/Charger	105-130 60Hz	975	13.85 max. @ no load 13.2 min. @ full load	55
14399	#7465	65 Amp Converter/ Charger	105-130 60Hz	1120	13.85 max. @ no load 13.2 min. @ full load	65

**7300 SERIES
POWER CENTER
ELECTRONIC
CONVERTER/CHARGER**

The RV Industry's Most Popular Power Center.

- Combines AC/DC distribution and converter/charger in one space-efficient package.
- Filtered power is free from spikes and surges.
- Minimizes interference with TVs, radios, and emergency channels per FCC Class B certification.
- Quiet operation.
- Accommodates five AC branches and nine DC fuse circuits (**fuses and circuit breakers not provided**). The full output rating is available for battery charging, virtually eliminating dead or drained batteries.
- 14" W x 11.75" H x 7" D; Weight: 20 lbs.
- Two-year warranty.

For smooth appliance
operation and bright
flicker-free lighting.



The electronic converter/charger provides
reliable battery charging and filtered output.

Order #	Model	Description	AC Input		DC Output	
			Volts	Branches	Volts	Amps
13046	#7345	Power Center with 45 ADC Converter/Charger	120	5	14.0 max. @ no load 13.2 max. @ full load	45
14518	#7345R	45 ADC Converter/Charger Lower Section Only	N/A	N/A	14.0 max. @ no load 13.2 max. @ full load	45
13047	#7355	Power Center with 55 ADC Converter/Charger	120	5	14.0 max. @ no load 13.2 max. @ full load	55
14517	#7355R	55 ADC Converter/Charger Lower Section Only	N/A	N/A	14.0 max. @ no load 13.2 max. @ full load	55

Safe,
convenient
power transfer
for 50 Amp,
120/240-volt
systems



MODEL ATS™ 501

With a flick of the generator switch, the ATS 501 line generator switch from Parallax transfers power smoothly between shoreline power and generator/secondary power source, regardless of line voltage conditions. ATS 501 is engineered for superior reliability in 50 Amp, 120/240-volt electrical systems (per the new UL Standard 1008). Electronic circuit board design is proven in extensive cycle testing to withstand heat and torque. The low-profile chassis measuring just 3-1/2" high allows mounting in areas not possible with other 50 Amp transfer switches, and installation can be made without cover removal. Manual shut-off for time delay optimizes use with inverters. 8-3/4" W x 3-1/2" H x 11-3/4" D. 7 lbs.

16600 50 Amp, 120/240 Volt
#ATS501 [1](#)


Progressive Dynamics Inc.
 The Source of Bright Ideas Since 1964

ENJOY CAMPING, NOT REPAIR SHOPS.

The really intelligent way to manage power in your RV!

Inteli-Power Series Converters and Power Centers from Progressive Dynamics have our exclusive Charge Wizard® technology. It constantly monitors voltage status and manages your RV battery and extends the life.

Standard features on Inteli-Power Converter and Power Centers:

- Reverse battery protection – prevents damage from improper battery lead connection.
- Filtered DC power delivery – provides safe and reliable service.
- Electronic current limiting – automatically reduces output voltage when maximum capacity is reached.
- Low line voltage protection – protects appliance from damaging low voltage irregularities.
- Our Inteli-Power Series™ models – Can recharge your RV battery to 90% efficiency in just a couple of hours using ChargeWizard technology.
- Variable speed intelligent cooling fan – automatically monitors unit temperature and activates fan at required speed.
- Hi voltage protection – protects unit from spikes or surges of voltage over 135 Volts.
- Automatic thermal shutdown – activates when unit temperature exceeds 150°F and protects unit from damage due to excessive heat.



Progressive Dynamics, Inc.

INTELI-POWER 9100®
 SERIES



9100 Series Inteli-Power™ Converters provide safe, reliable, filtered DC power to all 12-Volt lighting and appliance circuits. The built in Total Charge Management System (TCMS) allows for easy addition of the optional Charge Wizard,® a microprocessor-controller that constantly monitors the RV battery status and automatically selects one of four charging modes: **Boost Mode** - (14.4) to quickly bring the battery to 90% of full charge, **Normal Mode** - (13.6) safely completes the charge, **Storage Mode** - (13.2), automatically activates after 30 hours of non-use or **Desulfation Mode** - (14.4), for 15 minutes every 21 hours to prevent battery stratification and sulfation (the leading cause of battery failure).



Input: 105-130 VAC, Output: 13.6 VDC
 Dimensions: 4.5"H x 8.25"L x 7.25"W, Weight: 4 lbs.

12043 30 Amps #PD9130V 

Input: 105-130 VAC, Output: 13.6 VDC
 Dim.: 4.5"H x 8.25"L x 7.25"W, Weight: 4.5 lbs.

11727 40 Amps #PD9140AV 

Input: 105-130 VAC, Output: 13.6 VDC
 Dim.: 4.5"H x 8.25"L x 7.25"W, Weight: 4.5 lbs.

12438 45 Amps #PD9145AV 

Input: 105-130 VAC, Output: 13.6 VDC
 Dim.: 3.6"H x 8"L x 9"W, Weight: 5.8 lbs.

11728 60 Amps #PD9160AV 

Input: 105-130 VAC, Output: 13.6 VDC
 Dim.: 3.6"H x 11.5"L x 9"W, Weight: 7.5 lbs.

12045 80 Amps #PD9180V 



Plug-in a TCMS Charge Wizard®

The intelligent way to automatically charge batteries! Progressive Dynamics' Charge Wizard is a powerful microprocessor that turns your Inteli-Power 9100 Converter into an intelligent and completely automatic 12-VOLT charging system.

11726 Charge Wizard #PD9105V 

In Section D: Meters/Testers Wiring Fuses 12V Accessories Battery Accessories Chargers & Inverters Cords & Adapters Box/Hatch Switches

BUY QUALITY. BUY USA MADE CONVERTERS.

Progressive Dynamics Inc.
The Source of Bright Ideas Since 1964

INTELI-POWER 9200™ SERIES



Intel-Power 9200™ Series Converters with BUILT-IN Charge Wizard® will recharge your RV's battery to 90% in 2-3 hours. Many converters only have one charging mode, 13.6 VOLTS, which can result in battery boil-off. The 9200 Series converters have FOUR charging modes: BOOST (14.4 VOLTS), NORMAL (13.6 VOLTS), STORAGE (13.2 Volts) and DESULFATION (13.2 VOLTS with a 15 minute 14.4-VOLT burst every 21 hours).

Boost Mode – Rapidly brings RV battery up to 90% of full charge.

Normal Mode – Safely completes the charge or maintains the charge.

Storage Mode – Maintains charge with minimal gassing or water loss during periods of non-use or storage.

Input: 105-130 VAC, Output: 13.6 VDC
Dim.: 4.5"H x 8.25"L x 7.25"W, Weight: 4.5 lbs.

14390 45 Amps #PD9245CV 6

Input: 105-130 VAC, Output: 13.6 VDC
Dim.: 3.6"H x 8"L x 9"W, Weight: 5.8 lbs.

14391 60 Amps #PD9260CV 1

Input: 105-130 VAC, Output: 13.6 VDC
Dim.: 3.6"H x 8"L x 9"W, Weight: 5.8 lbs.

14392 70 Amps #PD9270V 1

Input: 105-130 VAC, Output: 13.6 VDC
Dim.: 3.6"H x 11.5"L x 9"W, Weight: 7.5 lbs.

14393 80 Amps #PD9280V 1



Retail Model Pendant

Plugs into the accessory port to show charger/converter status and allows for manual mode selection. The Pendant is included with all retail models.

S/O Retail Model Pendant #PD92201



INTELI-POWER 4600™ SERIES

MADE IN U.S.A.



Intel-Power 4600™ Series Lower Section Replacement/ Upgrade Converters for RV power systems are as close as you can get to a "universal" replacement. The 4600 Series Converters can be used to replace the lower section converters in Magnatec, Parallax and WFCO® power centers. They are MADE IN AMERICA and have the same impressive quality, performance, reliability and multi-patented features, including the incredible CHARGE WIZARD® built-in. The Intel-Power 4600™ Series Converters are WHAT YOU NEED FOR RELIABLE 12 VOLT POWER!

Size: 13.375"W x 8.125"D x 5.875"H

17382 35 Amp Converter/Charger Repl. Section #PD4635 4

17383 45 Amp Converter/Charger Repl. Section #PD4645 4

17385 55 Amp Converter/Charger Repl. Section #PD4655 4



INTELI-POWER 4000™ SERIES



The PD4000 Series "Mighty Mini", is a compact All-In-One AC/DC Distribution Panel and Intel-Power Converter with built-in Charge Wizard®. Compact & lightweight, the PD4000, has front access to a large wiring compartment. The Snap Lock cover stays shut while traveling yet opens with a touch. The AC Distribution Panel is rated for 120 VAC at 30 AMPS. The DC section has up to 12 branch fuse holders. The "Mighty Mini" is available in a 45 AMP model. Dim.: 12.25"W x 8.875"H x 5.625"D.

Note: 30 AMP main breaker and AC breakers are not included and shown for reference only.

10472 Distribution Panel 45 Amp. Mighty Mini #PD4045KV 6

10450 Replacement Converter 45 Amp. #PD4045CSV 6

INTELI-POWER 4500™ SERIES



INTELI-POWER 4300™ SERIES



The PD4500 Series is the Ultimate All-In-One AC/DC Distribution Panel and Intel-Power Converter/Charger. The AC Distribution Panel is rated for 240 VAC @ 50 AMPS.

The DC section has up to 18 branch fuse holders. Available with a 60 AMP Intel-Power Converter, it's the largest converter/ charger available in the industry. The patented built-in Charge Wizard® reduces RV battery recharge time and increases battery life, while reducing battery sulfation and maintenance problems. Panel Size: 11.85"W x 14.125"H x 8.5"D.
Note: AC breakers not included and shown for reference only.

S/O 60 Amp Converter/Charger Repl. Section #PD4560CSV

17392 60 Amp All In One Converter/AC/DC/ Panel #PD4560K12LV 1



The PD4300 Series AC/DC Distribution Panel has front access to a large wiring compartment and a snap lock cover that stays shut while traveling yet opens with a touch. The PD4300 is rated for 120 VAC at 30 AMPS, is available with either a 45 or 60 AMP Intel-Power converter and features a status indicator and mode control button for the built-in Charge Wizard®. The DC panel accommodates up to 12 branch fuse holders with maximum rating of 20 AMPS each. Dim.: 11.85"W x 14.125"H x 8.5"D.
Note: 30 AMP main breaker and AC breakers are not included and shown for reference only.

4300 Series Power Converter :

10501 45 Amp #PD4345K12LV 1

10515 60 Amp #PD4360K12LV 1

MADE IN U.S.A.



MADE IN U.S.A.



In Section D:	Meters/Testers	Wiring	Fuses	12V Accessories	Battery Accessories	Chargers & Inverters	Cords & Adapters	Box/Hatch	Switches
---------------	----------------	--------	-------	-----------------	---------------------	----------------------	------------------	-----------	----------

WFCO CONVERTERS, COME WITH THE FOLLOWING FEATURES AND SAFETY PROTECTION:

Features: • 3 Stage battery charging system. • Two 30 amp fuse positions on 8900 fuse boards. • 150 amp rated 8900 DC fuse boards. • LED fuse boards. • UL, cUL-Listed FCC Class B.

Protection: • Reverse Polarity. • Over Temperature. • Short Circuit. • Overload. • Over-current. • Current controlled fan.

Select WFCO products as your replacement converter of choice.

You can easily add a high performance converter to your RV. Take the guess work out of choosing the right replacement converter by using the replacement charts below. Dimensions are provided to assist with proper form and fit.



WF-8700 SERIES POWER CENTER CONVERTER/CHARGER AC/DC DISTRIBUTION

Get big performance up to 40 amps DC output. The WF-8700 series provide superior performance offering four to six 12 volt DC circuits and three to five 110 volts AC branch circuits (depending on the model).

CONVERTER/CHARGER, BLACK

- 15396** 25A, Black #WF-8725-PB 1
- 15445** 35A, Black #WF-8735-PB 1

CONVERTER/CHARGER, BROWN

- 15393** 12A, Brown #WF-8712-P 1
- 15395** 25A, Brown #WF-8725-P 1
- 15415** 35A, Brown #WF-8735-P 1
- 16731** 40A, Brown #WF-8740-P 1

POWER CENTERS						
WFCO Mfr#	Description	Dimensions Cut-out (W x H x D)	Progressive Dynamics	Parallax	Atwood	Elixir
8712	12 Amp DC	10-7/16 x 6-1/8 x 3-3/4	-	-	-	ELX12
8725	25 Amp DC	10-7/16 x 6-1/8 x 3-3/4	-	-	-	ELX20/25
8735	35 Amp DC	10-7/16 x 6-7/8 x 3-3/4	-	-	-	-
8740	40 Amp DC	10-7/16 x 6-7/8 x 3-3/4	-	-	-	-
8935	35 Amp DC	12-3/16 x 10-7/8 x 7-1/4	-	7335	-	ELX35
8945	45 Amp DC	12-3/16 x 10-7/8 x 7-1/4	PD4045	7345	-	ELX45
8955	55 Amp DC	12-3/16 x 10-7/8 x 7-1/4	-	7355	APS5530	ELX60
8965	65 Amp DC	12-3/16 x 10-7/8 x 7-1/4	-	-	-	-
8975	75 Amp DC	12-3/16 x 10-7/8 x 7-1/4	-	-	-	-

DECK MOUNT CONVERTERS							
WFCO Mfr#	Description	Dimensions (W x H x D)	Progressive Dynamics	Parallax	Atwood	Iota	Elixir
9835	35 Amp DC	4-5/8 x 4 x 7-1/2	PD9130	7430	32	DSL-30	-
9845	45 Amp DC	4-3/4 x 4 x 8-3/4	PD9140/45A& PD9245	7445	45	DSL-45	-
9855	55 Amp DC	4-3/4 x 4 x 8-3/4	-	7455	55	DSL-55	-
9865	65 Amp DC	5-1/8 x 4 x 10-1/4	PD9160A/ PD9260	7465	-	-	DM6000
9875	75 Amp DC	5-1/8 x 4 x 10-1/4	PD9170A/ PD9270	-	35414	DSL-75	DM8000
68100	100 Amp DC	7-5/8 x 4 x 12-11/16	PD9180A/ PD9280	-	-	DSL-90	-

MAIN BOARD ASSEMBLY REPLACEMENT		
WFCO Mfr#	Description	Parallax
8945REP	45 Amp DC	7345
8955REP	55 Amp DC	7355
8945MBA	45 Amp DC	7145
8955MBA	55 Amp DC	7155

MAIN BOARD ASSEMBLIES

Replaces the lower power converter section on any WF-8900 Series converter. Installs easily with only 4 screws and five wires.



- 15501** 35Amp DC #WF-8935-MBA 1
- 15516** 45Amp DC #WF-8945-MBA 1
- 15528** 55Amp DC #WF-8955-MBA 1
- 15733** 65Amp DC #WF-8965-MBA 1
- 15757** 75Amp DC #WF-8975-MBA 1



WF-8900 SERIES POWER CENTER CONVERTER/CHARGER AC/DC DISTRIBUTION

The WF-8900 series converter provides superior performance offering eleven 12 volt DC circuits and up to five 110 volts AC circuits.

CONVERTER/CHARGER, BLACK

- 15482** 55A, Black #WF-8955-PECB 1
- 15497** 65A, Black #WF-8965-ANPB 1

CONVERTER/CHARGER, BROWN

- 15458** 35A, Brown #WF-8935-ANP 1
- 15462** 45A, Brown #WF-8945-ANP 1
- 15481** 55A, Brown #WF-8955-PEC 1
- 15496** 65A, Brown #WF-8965-ANP 1
- 15499** 75A, Brown #WF-8975-ANP 1



WF-9800 SERIES DECK-MOUNT CONVERTER/CHARGER

The versatile, advanced power source solution. Output ratings from 35 amps DC to 100 amps DC. Convenient deck-mount installation.


WF-9800 SERIES

- 15761** 35A #WF-9835 1
- 15765** 45A #WF-9845 1
- 16843** 55A #WF-9855 1
- 15797** 65A #WF-9865 1
- 15824** 75A #WF-9875 1

UNIVERSAL CONVERTER REPLACEMENT KIT

8900REP models make it easy to replace certain brands of converters with removable converter section.

- 15832** 45A #WF-8945REP 1
- 15839** 55A #WF-8955REP 1



In Section D:	Meters/Testers	Wiring	Fuses	12V Accessories	Battery Accessories	Chargers & Inverters	Cords & Adapters	Box/Hatch	Switches
---------------	----------------	--------	-------	-----------------	---------------------	----------------------	------------------	-----------	----------

Atwood® by **FORTRON**

POWER CONVERSION AND DISTRIBUTION

CONVERSION PACKAGE

CLEAN POWER – CLEAN DESIGN

The SRV Series offers a wide range of power in a compact design weighing just 6 pounds. Atwood technology maintains safe, cool, reliable converter/charging operation, ensuring the performance of electrical systems with sophisticated controls. The thermostatically-controlled cooling fan also reduces noise and increases warm-weather performance. The SRV's circuitry includes over-temperature and over-current protection, safeguarding against power supply damage. Two external fuses provide "reversed battery" protection, preventing damage caused by cross-wiring. SRV filtered power provides smooth, optimum DC appliance operation, and the full output rating is available for battery charging. **Common features:** • Regulated output voltage ensures against erratic charging and damage to amenities. • Over-current protection prevents battery damage caused by over-charging. • Short circuit protection prevents damage to power supply. • Reverse battery hook-up protection prevents power supply damage due to cross-wiring. • Fan cooled, prevents unit from over-heating. • 100% burn-in tested ensures stringent quality assurance. • 2-year limited warranty. • UL/cUL certified.



CONVERTER/CHARGER & DISTRIBUTION PACKAGE

COOL, QUIET CONVERTER/CHARGING

With the wide selection of converter/charger output ratings, you can have "Total Package" convenience for easy replacement of other converter/chargers in the aftermarket. The Total Package carries a standard Atwood 2-yr. limited warranty, and is UL/cUL certified. Atwood® by Fortron has developed electronic switch mode technology that maintains safe, reliable, and cool operations. The cooling fan is thermostatically controlled, which also reduces noise and improves performance in warmer climates. The converter/charger circuitry includes over-temperature and over-current protection, safeguarding against power supply damage. Two external fuses provide "reversed battery" protection, preventing damage caused by cross-wiring from battery terminals.



Denotes Limited Supply!

CONVERTER SPECIFICATIONS

Order #	Model	Amps	Cut Out Size	External Dimensions	Input Voltage AC	Output Voltage DC	Input Current Amps	Output Current Amps	Breaker Config. AC	DC Branch Circuits	Price
CONVERTER ONLY											
13574	SRV32	32	–	10.35" W x 7.75" D x 3.5" H	105/130	13.6	7	32	–	–	
13575	SRV45	45	–	10.35" W x 7.75" D x 3.5" H	105/130	13.6	10	45	–	–	
13576	SRV55	55	–	10.35" W x 7.75" D x 3.5" H	105/130	13.6	13	55	–	–	
13577	SRV75	75	–	10.35" W x 7.75" D x 3.5" H	105/130	13.6	15	75	–	–	
CONVERTER WITH PANEL (STANDARD BREAKER)											
13580	TP3-5530SS	55	12.5" W x 11.25" H	14" W x 12" H x 7" D	105/130	13.6	13	55	Main + 5 Branch	15	



PARKPOWER by MARINCO ONE-PIECE ADAPTER

83A-One-Piece Adapter, 30A Locking to 15A Straight Blade. Female Connector: 30A 125V Locking, attaches to cordset or trailer inlet. Male Plug: 15A 125V Straight Blade, attaches to park receptacle or cordset.

16661 Female: 30A 125V Locking, Male: 15A 125V Straight Blade
(Not for sale in Canada) #83A 1



PARKPOWER by MARINCO 15 & 20AMP PRODUCTS

125-Volt Power Inlets: Straight blade inlet. • Use 15Amp with any standard 15A extension cord; use 20Amp with any standard 20A extension cord. • UV resistant housing and cap.

Power Inlet:

14149 15A, White #150BBIWRV 1

79862 15A, Black #150BBI.RV 1

14150 20A, White #200BBIWRV 1



30 AMP/125V, LOCKING PRODUCTS



30 AMP ACCESSORIES

Marine grade construction, 5 year mfr. warranty. Stainless steel fasteners. Contoured weather-proof cover design allows better grip. Yellow.

30 Amp, 125 Volt Accessories:

16641 Male Plug #305CRPN 1

16640 Female, Locking Connector #305CRCN 1

16684 Weatherproof Cover with Sealing Ring for 20 & 30 Amp Female Connectors #103RN 1

In Section D:	Meters/Testers	Wiring	Fuses	12V Accessories	Battery Accessories	Chargers & Inverters	Cords & Adapters	Box/Hatch	Switches
---------------	----------------	--------	-------	-----------------	---------------------	----------------------	------------------	-----------	----------

ParkPower
by Marincó



14292

14293

PARKPOWER by MARINCO 30 AMP PRODUCTS

FEMALE CONNECTOR

• 30A 125-V locking connector. • Corrosion resistant materials. • Use with 103RV, 103ELRV for weatherproof seal.

14292 30A 125-V Connector
#305CRV 4

WEATHERPROOF COVER

• Weatherproof cover with threaded ring. • Use with 305CRV connector for a weather proof seal.

14293 Weatherproof Cover f/305CRV
#103RV 4



16639

16638

14294

POWER INLETS

30A 125V Power Inlet (Standard White).

Standard 30 Amp 125 volt non-metallic power inlet; 3-wire Locking. Marine grade UV stabilized glass-filled polyester construction. Soft Touch cap design - cap stays open in upright position; a "soft touch" lowers the cap.

16638 W/4-Way Right Angle Rear Safety Enclosure, Marine Stainless Steel Trim
#301EL-B 1

Standard Power Inlet. • 30A 125-V locking type. • Glass-filled polyester. • Easy Lock™ system. • Watertight. • 4-way right angle rear safety enclosure. • Stainless steel trim. • Accepts all Marincó detachable power cordsets.

14294 30A 125-V Power Inlet
#301ELRV 4

Stainless Steel Power Inlet. 30A 125V Locking. 316 stainless steel. Easy Lock™ System. Soft Touch™ cap design. Watertight cap. Accepts all Marincó detachable power cordsets. Locking cap.

16639 Stainless Steel w/8-Way Right Angle Rear Safety Enclosure
#303SSEL-B 1

With
LED power
indicator



RODALE PIGTAIL ADAPTER

• Adapts power from 30amp to 15amp cordset and 30amp to 50amp. • Includes threaded ring for easy connect and disconnect. • Constructed with heavy-duty cable and watertight connections for safe, outdoor use.

10633 Pigtail Adapter with Locking Screw, 30A female to 15A male (Not for sale in Canada) #P125-30FL-125-15ML 140

ParkPower
by Marincó



11743

11744

PARKPOWER by MARINCO 30A PRODUCTS

30A ADAPTER, 125-V

• 30A straight blade (2-pole, 3-wire) RV plug with 30A female locking connector. • Includes Easy Lock™ ring and threaded ring for connector.

11743 Adapter, 30A Male RV to 30A Locking Female (Not for sale in Canada)
#1PCMRV 1

RV 30A LOCKING CORDSET

• Super flexible 10/3 cable. • Easy Lock™ system. • Includes threaded ring and Easy Lock ring. • Line-up ridge locator (orients ground blade). • Watertight molded plug & connector ends. • High quality marine-grade construction.

11744 30A RV Cordset, 2-Pole, 3-Wire, 25ft. #25PCMRV 1

ParkPower
by Marincó



PARKPOWER by MARINCO GENERATOR ADAPTER

• 30A locking male plug with 30A RV female connector. • Use to connect RV cordset to generator with 30A locking power outlet.

14147 Generator Adapter 30A (Not for sale in Canada) #125A 1

50A 125/250V 3-POLE, 4-WIRE LOCKING

NEMA
SS-150A 125V
LOCKINGNEMA
SS-250A 125/250V
LOCKING

50 AMP 125V, LOCKING & 50 AMP 125/250V, LOCKING PRODUCTS



14295

14296

ParkPower
by Marincó

PARKPOWER 50AMP PRODUCTS

Female Connector: 50A 125/250-V. Easy to install. Use with 50A 125/250-V 4-wire cable.

14295 50A 125/250-V Female Connector
#6364CRV 4

Weatherproof cover with threaded ring for 50A.

14296 Weatherproof Cover f/6364CRV
#7715CRV 4



16650

16656

MARINCO CONNECTOR & COVER

16650 Fem. Locking Connector, 50A125/250V
#6364CRN 1

Weatherproof Covers for 50 Amp Connectors

16656 Cover w/Threaded Ring for #6360CRN or #6394CRN #7715CRN 1

ParkPower
by Marincó



14011

16654

RV POWER INLETS

50A 125/250V Stainless

Steel Inlet. Does not include rear safety enclosure with strain relief. 4 wire system. UL & CSA approved.

16654 50A125/250V, Stainless Steel, 4-Wire w/Easy Lock™ System #6373EL 1

Standard 50A Power Inlet. 50A 125/250-V. Glass-filled polyester. Easy Lock™ system. Watertight. Rear safety enclosure with strain relief. Stainless steel trim.

14011 50A 125/250-V Power Inlet
#6353ELRV 1

POWER CORDS & ACCESSORIES

ELECTRICAL

D

In Section D:	Meters/Testers	Wiring	Fuses	12V Accessories	Battery Accessories	Chargers & Inverters	Cords & Adapters	Box/Hatch	Switches
---------------	----------------	--------	-------	-----------------	---------------------	----------------------	------------------	-----------	----------



PARKPOWER by MARINCO RV 30 AMP RIGHT ANGLE LOCKING CORDSET

- GripLock™ handle design for easy hook-up and correct blade alignment with inlet, even in darkness.
- Super flexible 10/3 cable.
- Watertight molded plug and connector ends.
- High quality construction.
- Includes threaded ring and Easy Lock™ ring.

16835 30A RH Angle Locking Cord, 30' (Not for sale in Canada) #30RPCR 4

ParkPower by MarincO 50A LOCKING POWER CORD PLUS™ CORDSET WITH RV PLUG



- LED power indicator light.
- Thumbprint locator.
- Molded straight blade plug.
- Super flexible 6/3-8/1 cable.
- Comfort grip connector.
- Easy Lock™ System.
- Includes threaded ring and Easy Lock™ ring.
- Watertight molded plug & connector ends.
- High quality marine-grade construction.

16666 50A Cordset, 3-Pole, 4-Wire, 25ft. #6152SPPRV-25 1

COOPER WIRING 3-WIRE U-GROUND RUBBER CAP

Parallel blade with cord clamp. Rubber cap with reinforced zinc-plated, steel plate (.031" thick). Fiber cover included. Cord grips accept all cords from $\frac{19}{64}$ " to $\frac{9}{16}$ " dia. solid brass with #6-32 brass terminal screws backed out and staked. Grounding screw. Rated: 15A-125V. 1875 Watts.



10481 3-Wire Male Cord Connector #2867-BOX 1



COOPER WIRING HEAVY DUTY CORD CONNECTOR

2-pole, 3-wire with cord clamp. Molded rubber construction will not chip or wear away, impact and water resistant. Steel cord clamp takes cords from $\frac{5}{16}$ " (.312) to $\frac{5}{8}$ " (.625) in diameter. Rated: 15A-125V. Capacity: 1875 Watts.

10480 Heavy Duty Female Cord Connector #2887-BOX 5



PARKPOWER by MARINCO ADAPTERS

No matter what your RV's power needs are, ParkPower adapters allow you to use a variety of RV park, storage or home electrical service options. ParkPower "Y" adapters will also solve different electrical power hook-up needs.

25 FOOT RV ADAPTER

- 50Amp 125/250-V locking connector with 30Amp 125-V RV straight blade plug (2-pole, 3-wire).
- Allows coaches with 50A locking service to access 30A RV park service.

14012 RV Adapter 50A/30A, 25' (Not for sale in Canada) #124ARV-25 1

1 FOOT RV ADAPTER

- Same as above, 1' long.

14013 RV Adapter 50A/30A (Not for sale in Canada) #124ARV 8

ADAPTER

- 50A locking connector with 15A straight blade plug.
- Comfort grip connector.
- Easy Lock™ system.
- Includes threaded ring. Allows coaches with 50A locking service to connect to household power. Female 50A, 125/250-V 3-pole, 4-wire locking to male 15A 125-V.

14298 50A Twist Lock to 15A Straight (Not for sale in Canada) #150SPPRV 4

Y ADAPTER

- 50A 125/250-V RV plug with two 30A female connectors.
- Not weatherproof.

14148 50A 125/250-V Male 3-Pole, 4-Wire to Two Female 30A 125-V 2-Pole, 3-Wire RV (Not for sale in Canada) #169AYRV 1



PARK POWER by MARINCO CONVERSION KITS

MarincO ParkPower makes hooking up your RV's electrical service much easier. The ParkPower detachable power system uses the same rugged corrosion-resistant components developed for marine use. At the core is the MarincO inlet and connector with weatherproof cover. After installing the inlet on the side of the RV, the original power cord that came with the RV can be modified by installing the connector and cover on the severed end. Detachable power allows you to use a variety of power cords and adapters to make hook-up easier. All components are of the highest quality construction and built to give years of service. 5 year warranty. Easy-to-follow installation instructions make conversion to detachable power a snap.

50A CONVERSION KIT

- Converts 50A hard wired RV power hook-up to detachable power hook-up.
- Easy Lock™ system.
- Has everything needed for conversion:
 - 6344EL-BRV 50A contoured power inlet.
 - 6364CRV 50A female connector (installs to RV power cord).
 - 7715CRV weatherproof cover with threaded ring.
 - Mounting gaskets.
 - Electrical box.
 - Strain relief.

13671 50A Conversion Kit (Not for sale in Canada) #50 ARV KIT 1



30A CONVERSION KIT

- Converts 30A hard wired RV power hook-up to detachable power hook-up.
- Easy Lock™ system.
- Includes everything needed for conversion:
 - 304EL-BRV 30A contoured power inlet.
 - 305CRV 30A female connector (installs to RV power cord).
 - 103RV comfort grip weatherproof cover with threaded ring.
 - Mounting adapters and gaskets.
 - Electrical box.
 - Strain relief.

13670 30A Conversion Kit (Not for sale in Canada) #30ARVKIT 4

COOPER Bussmann



COOPER WIRING MOTOR BASE

Weatherproof parallel grounding male motor base 2-pole, 3-wire. For use on mobile homes, trailers, campers, etc. Horizontal snap open lid. Stainless steel hinge spring. Aluminum finish brass plate with weatherproof gasket. Mounting screws furnished. Individually boxed. Will take up to 1-17/32" dia. female connector. 15 Amp, 125 Volt.

11156 Motor Base #S3999 **15**



5/8" barrel



JR PRODUCTS KEY LOCKS

Cam lock for replacement in B&B Molder hatches as well as any other place a barrel lock is needed. Comes keyed for a 751 style key to match other compartments and hatches.


751 Key Code Lock Cam with key, 5/8" barrel:

43018 Long, 1-1/8" Blade #00100 **1**

43026 Short, 5/8" Blade #00E00 **1**



*1-1/8" cam (term used for length of blade)



RV DESIGNER HATCH LOCK

Used on water, electric, gas hatches etc.

Clamshell packaging: 3" W x 5" H x 1" D, C:

44842 1-1/8" Hatch Lock with 1-1/8" cam*, 5/8" barrel #L100 **1**

44843 Hatch Lock with 5/8" cam, 5/8" barrel #L110 **1**

44844 Replacement Key, Code 751, Pk/2 #L200 **1**

JR PRODUCTS HATCH INSTALLATION KIT

Installation kit with everything you need to replace or install a hatch. Includes screws and premium butyl tape for a proper seal.

65439 Small Hatch Installation Kit (25" butyl tape & 12 screws) #04205 **36**

65440 Large Hatch Installation Kit (36" butyl tape & 10 screws) #04195 **36**



JR PRODUCTS HATCHES

ELECTRICAL HATCH WITHOUT BACK

Keeps electrical connection tamper-proof while in use and during travel. Provides bigger opening for easy access to power cord. Makes it easier to handle larger service cords. Includes RVIA-approved warning tag and instructions. 8" x 8 1/2" overall (cutout size: 6 7/8" H x 6 3/8" W).

25416 Non-Locking Utility Hatch with Thumb Latch, Polar White #22D32-A **12**

25417 Locking RV Electrical Hatch without Back, Polar White #22132-A **24**

LOCKING ALL-PURPOSE RV UTILITY HATCH WITHOUT BACK

Shallow all-purpose locking access hatch. Provides easy access to gas fillers, sewer gate valve. Keeps 5th-wheel jack mechanism safe and secure. Many other possible uses. Cutout size: 6 7/8" H x 6 3/8" W. Overall size: 8 1/2" H x 8" W. Blank tag. Without back. Polar white.

25415 Locking Hatch #21102-A **12**

MULTI-PURPOSE HATCH WITHOUT BACK

Extra large utility hatch. Flush mounted design will fit over any opening within measurements. Reinforced molding process makes the door even more durable. Comes with a key latch for added security. The hinge design makes the door replaceable if needed. Dimensions: cut out dim. 9-1/8" x 8"; outside dim. 11-3/8" x 10-3/8".

27809 Multi-Purpose Hatch w/Key Lock, Polar White #NBF02 **1**



25412



27809

MEDIUM ELECTRIC CABLE HATCH

Impact and fade-resistant Rovel® keeps electrical connection tamper proof while in use or traveling. Provides bigger opening for easy access to power cord. Makes it easier to handle larger (50 amp) service cords. Includes RVIA-approved warning tag and instructions. Overall size: 6 1/2" H x 7 3/8" W x 2"D. (Cutout size: 4 3/4" H x 5 7/8" W.)

25412 Polar White #E7132-A **12**

LOCKING HATCH KEYS

Package of 2 replacement keys for locking hatch.

44846 Square Head #DECO-A **12**

49399 Round Head #751-A **12**



ZEBRA RV ACCESSORIES CABLE HATCH

- Safely allows cord access while protecting your RV from pests.
- Made of durable polypropylene with locking latch.

Cable Hatch With Locking Latch, Packaged:

20176 Colonial White #RM207C **12**

20178 Polar White #RM208P **12**



In Section D:	Meters/Testers	Wiring	Fuses	12V Accessories	Battery Accessories	Chargers & Inverters	Cords & Adapters	Box/Hatch	Switches
---------------	----------------	--------	-------	-----------------	---------------------	----------------------	------------------	-----------	----------



28698



28697

JR PRODUCTS MULTI-PURPOSE HATCHES

WITH FLAT BACK

Great hatch for customizing your application. Constructed for long life and will not fade or discolour due to UV rays or weather. Hatch is paintable to match the exterior of any RV with no preparation of its surface. Designed with a flat back to fit almost any use.

With Flat Back, Polar White:

28696 Cutout dim.: 4-3/8" x 3-1/8"; outside dim.: 6-1/4" x 5" #D6102-A 1

28698 Cutout dim.: 4-3/4" x 5-7/8"; outside dim.: 6-1/2" x 7-5/8" #G8102-A 1

WITHOUT BACK

Constructed of high-quality plastic for durability. Will not discolour and resists fading and road salt. Paintable to match any exterior with no preparation. It is constructed with an open back and a 1-1/8" collar for a variety of uses. Cutout dimensions. 4-3/4" x 5-7/8"; outside dimensions. 6-1/2" x 7-5/8". Polar White.

28697 Multi-Purpose Hatch, Without Back #E8102-A 1



Large electrical hatch comes with two vermin doors that accept up to a 50 Amp cord. Built with a high quality plastic that won't fade or discolour. Resists road salts and acids. Paintable to match any exterior. Cutout dim.: 6" x 11-1/16"; outside dim.: 7-3/4" x 12-5/8". Polar White.

28699 Utility Center #ZH152-A 1

RV DESIGNER UNIVERSAL ROUND ELECTRIC CABLE HATCHES



Includes two interchangeable rear buckets. One fits 3" hole, one fits 3-1/2". 3" bucket accepts 30 amp cord & plug; 3-1/2" accepts 30 or 50 amp. Unique design diverts water. Gasket & screws included; everything you need for easy installation. 5-1/8" diameter faceplate covers holes & marks from most other hatches. UV protected plastic. 1-yr. warranty.

This is the hatch you want!



Universal Round Electric Cable Hatch, Full-color Box of 5" x 5" x 5":

10639 White #B101 6

10642 Colonial White #B103 6



20173

20170



ZEBRA RV ACCESSORIES ELECTRICAL CABLE HATCH

- Made of durable ABS plastic with snap-like catch. • 1" Back Opening. • Safely allows cord access while protecting your RV from pests.



Cable Hatch, Packaged:

20170 Colonial White #RE147C 12

20173 Polar White #RE147P 12

COOPER WIRING GROUND FAULT INTERRUPTER

Ground fault current interrupter receptacles. Designed to protect people from line-to-ground electrical shock hazards. Specification grade

with a GFCI rating of 15 amps, 120 volts at receptacle, 20 amps, 125 volt feed-through. UL listed 1-1/8" receptacle depth for extra wallbox room. Fits standard 2-1/2" box. With indicator light.



Ground Fault Interrupter:

13038 Brown #VGF15B 10

13219 Ivory #VGF15V 10

13039 White #VGF15W 10

Wall Plate Only for Ground Fault Interrupter:

10490 Brown Plate #2151B-BOX 10

10491 Ivory Plate #2151V-BOX 10

16241 White Plate #2151W-BOX 10

RV DESIGNER WEATHER- PROOF OUTLET COVER

Weatherproof replacement cover for duplex outlet. Works for electrical, TV, phone etc. 4-3/4" x 2-3/4". Metal base with white plastic cover. Gasket & mounting screw included. PK/1



46241 Weatherproof Cover #E365 12

RV DESIGNER WEATHERPROOF COVER

For GFI outlet. Clamshell packed.

85724 Weatherproof Cover, White #E465 12



COOPER WIRING DUPLEX RECEPTACLE

Universal grounding duplex receptacle. 2-pole, 3-wire. Automatic self-grounding mounting screws ground to any grounded metallic wall box, eliminating the use of a bonding jumper. Has wire pressure terminals, 15A-125V rating.

Duplex Receptacle, CD/1:

10482 Brown #270B 1

10484 Ivory (Shown) #270V 1

12339 White #270W 1



KING CONTROLS 12V DIMMER SWITCH

12-volt dimmer switch is noiseless and low profile to fit many locations (1.7" x 1.4" x 0.7"). It works with incandescent and fluorescent fixtures. Handles up to 7.5-amps. Features OFF position.



10432 12V Dimmer Switch #9101 5

JR PRODUCTS HATCHES

ECONOMY SQUARE ELECTRIC CABLE HATCH

All white flush mounting with slide catch cover. 4 $\frac{3}{8}$ " overall dia. 3" cut-out dia. 1 $\frac{3}{4}$ " deep.



Economy Square Electric Cable Hatch:

12062 Colonial White #S-27-14-A 36

17236 Polar White #S-27-10-A 36



ECONOMY ROUND ELECTRIC CABLE HATCH

Mount flush with outside of wall of trailer. Easy to install. 3" cut-out, 4 $\frac{1}{4}$ " flange.

Economy Round Electric Cable Hatch:

12954 Colonial White #S-23-14-A 36

15901 Polar White #S-23-10-A 36

ROUND CABLE HATCH WITH BACK


Low profile design. U.V. stabilized, fade and impact resistant. Easy installation with snap lock. Vermin door will accept up to 50 amp cord. 4.5" dia. overall; 3.5" cut-out size.



Round Electric Cable Hatch with Back:

78834 Colonial White #370-1-A 1

78835 Polar White #370-2-A 48



DELUXE ROUND ELECTRIC CABLE HATCH

Re-designed to be sturdier than other round electric cable hatches. The outside collar is wider to cover up any pre-existing screw holes. The hinge is extra heavy duty. Use this when an extra sturdy hatch is required. The hatch is constructed not to fade or discolor due to weather or chemical action. Vermin door will accept a 30 or 50 amp cord. Replaces any round hatch up to 4-1/2". Polar White.

Round Electric Cable Hatch:

45262 Black #541-3-A 48

65841 Polar White #541-2-A 48




WINEGARD DUPLEX RECEPTACLE COVER

Weatherproof duplex electrical outlet cover to be used with any standard 117V duplex outlet.



14614 Cover, Ivory #WB-1110 12



Receptacle Blank

COOPER WIRING PLATES & RECEPTACLES

WALL PLATE FOR RECEPTACLE

Non-flammable Bakelite; easy to clean. 2 $\frac{3}{4}$ " x 4 $\frac{1}{2}$ ". Short screws included.

Wall Plate for Duplex Receptacle:

12197 Brown #2132B-BOX 5

12198 Ivory #2132V-BOX 5

12337 White #2132W-BOX 5

BLANK WALL PLATE

This blank wall plate is made of easy-to-clean, fireproof melamine plastic. Plate provides a neat cover-up for junction box areas and outlets no longer in use.

Blank Wall Plate

12199 Brown #2129B-BOX 10

12200 Ivory #2129V-BOX 10

12338 White #2129W-BOX 10

CHROME ROCKER SWITCH

On/Off rocker switch mounted on chrome mini plate. Individually bagged with header card. 10 amp rated, 12 volt.

10158 Wall Switch #11-0190 24



SEASENSE TOGGLE SWITCH BOOT

Flexible molded splash-proof boot for toggle switch.

14161 Toggle Boot, 1/Cd. #50031200 6



POLLAK TOGGLE SWITCHES FOR UNIVERSAL APPLICATIONS

Heavy duty (U.L. Listed). 20 amp rating for heavy duty applications. 20 amps 6-24 volts DC, U.L. listed, 20 amps 125 volts, 10 amps 250 volts. All with 1 $\frac{5}{32}$ " diameter, 3/8" long mounting stem. Furnished with Knurled face nut, hex back nut, and terminal screws. Chrome plated bat handle.

Single pole single throw. Two positions: Off/Momentary on. 2 screw terminals. CD/1.

12365 On-Mom #34-570V 1

Single pole single throw. Two positions: On/Off. 2 screw terminals.

12370 On-Off #34-571V 10

Single pole double throw. 3 positions: Momentary On/Off/Momentary On. 3 screw terminals.

12366 On-Off-Mom #34-575 5

Single pole double throw. Three positions: On/Off/On. 3 screw terminals.

12371 On-Off-On #34-573V 10



JT&T STANDARD DUTY 12V TOGGLE SWITCHES

Standard duty 16 Amp @ 12 Volt, except as noted. These switches use #11693 round panel mount.

11692 Non-Illuminated, On/Off, Black #2640H 6

11684 Illuminated Switch, On/Off, Blue #2616J 6

11685 Illuminated Switch, On/Off, Amber #2617J 6

JT&T ROCKER SWITCHES

Standard duty 16 Amp @ 12 Volts. On/Off SPST. 1 $\frac{1}{8}$ " L x 1 $\frac{1}{2}$ " W x 1" D.



Illuminated Switch (use #11694 Panel Mount):

11682 Red #2602J 6

12101 Green #2605J 6

753788 ^{LS} Blue #2606J 6

12100 Amber #2607J 6

Non-Illuminated Switch (use #11694 Mount):

12093 Black #2600J 6